



ROTO-PRIME®

*Priming-Assisted
Petroleum Pumps*

GR
GORMAN-RUPP
PUMPS

The Pump People®



ROTO-PRIME®

Priming-Assisted Petroleum Pumps

Roto-Prime® priming-assisted centrifugal pumps are specifically designed for pumping petroleum products, petrochemicals and solvents. The Roto-Prime design incorporates a variable capacity vane pump which quickly and automatically evacuates air and vapor, making the pump ideal for loading and off-loading transports and stripping hoses.


Roto-Prime® Provides Automatic, Positive Pumping

Roto-Prime® pumps are actually two pumps in one: a variable capacity vane pump used during the priming cycle, and a standard centrifugal pump to move the liquid.

Whenever air or vapor is present at the start of the pumping operation – or when there is a loss of suction because of air or vapor during pumping – the priming pump automatically moves air and vapor from the suction line to discharge line. Once the flowing liquid from the centrifugal portion of the pump builds up sufficient pressure in the discharge system, the pressure backs up through a tube to act on the bottom of the priming pump's movable slide block, placing it in a neutral position during normal operation.


- **Full Priming**

With air or vapor in the lines, pressure of the spring on top of the movable slide holds the priming pump in full pumping position.



- **Partial Priming**

As the pump evacuates air and vapor from the lines, liquid pressure builds up on the underside of this slide, moving it upward toward neutral.




- **Neutral**

When air and vapor are removed, liquid pressure equalizes spring pressure and the pump automatically slides into neutral...where it remains until air and vapor again appear in the system.



GORMAN-RUPP ROTO-PRIME®

The Right Pump For The Job



The GRP33-08 air release valve evacuates air in the suction line to ensure positive self-priming even when pumping against moderate to high static heads. The standard air release valve is equipped with a stainless steel float which offers enhanced performance in all applications including liquids with high concentrations of ethanol.



01 | Suction Inlet

02 | Discharge Outlet

03 | Balanced Impeller

04 | Volute

05 | Variable Displacement Priming Pump

06 | Mechanical Seal

07 | Sealed End Ball Bearings

08 | Optional Air Release Valve

Specifications

Pump Size Range: 3" (75 mm) x 2" (50 mm) to 6" (150 mm) x 5" (125 mm)

Max. Capacity: 1460 GPM (92.1 lps)

Max. Head: 390' (118.9 m)

Max. Operating Speed: RS Series (single volute) 1750 rpm, RD Series (double volute) 3450 rpm

Materials of Construction: Aluminum Impeller, Ductile Iron or Cast Steel Housing, Steel or Stainless Steel Shaft, Fluorocarbon Mechanical Shaft Seal*


*Optional seals available to handle a variety of liquid formulations. Consult factory for details.

Optional Accessories


- Stainless Steel Shafts
- Bronze Impellers
- Companion Flanges
- Swing Check Valves
- Specialized Mechanical Seals
- Air Release Valve
- Available in a variety of motor and base configurations

Pump Performance Data

RS Series



RD Series



FLUID-HANDLING EQUIPMENT DESIGNED WITH YOUR NEEDS IN MIND



★ Manufacturing Facilities
● Distribution Centers

Gorman-Rupp USA
Mansfield, Ohio, USA

Gorman-Rupp Canada
St. Thomas, Ontario, Canada

Gorman-Rupp Europe
Culemborg, Netherlands
Namur, Belgium

Gorman-Rupp Africa
Cape Town, South Africa
Durban, South Africa
Johannesburg, South Africa (Headquarters)

Distribution Centers
Dubai, United Arab Emirates
Grand Prairie, Texas, USA
Culemborg, Netherlands

Engineering and manufacturing superiority has been the hallmark of Gorman-Rupp since our inception in 1933. Today we bring our products to life in some of the most efficient, modern and state-of-the-art manufacturing facilities in the world. Gorman-Rupp has a selection of nearly 3,000 pump models, and our world-class team of distributors has worked closely with thousands of end users around the world. We have the proven expertise and the resources to specify, manufacture, test and service your pump, and to ensure reliable performance for the long haul.



GORMAN-RUPP PUMPS

P.O. BOX 1217
MANSFIELD, OHIO 44901-1217 | USA
TEL: 419.755.1011 | FAX: 419.755.1251

GRPUMPS.COM



The Pump People®